


<b>Display Type</b>	30.0" (30.0" VIS) LCD screen
<b>Pixel Pitch</b>	0.502 mm X 0.502 mm
<b>Display Area(Visual)</b>	25.3" x 15.2" (643 mm x 386 mm)
<b>Dimension(W x H x D)</b>	697.8 x 431.8 x 50.9 mm
<b>Electronical Interface</b>	LVDS
<b>Backlight Unit</b>	16 CCFL Lamps
<b>Number of color</b>	8 bits
<b>Display Colors</b>	16.8 M Color
<b>Luminance</b>	450 cd/m2
<b>Contrast Ratio</b>	400:1
<b>Viewing Angle</b>	H: 176°, V:176°
<b>Response Time (Rise/Decay)</b>	25 ms
<b>Module Resolution</b>	1280 x 768 (WXGA)
<b>Surface Treatment</b>	Hard Coating (3H) Anti-glare
<b>MTBF</b>	50000 Hr ( Back Light : 40000 Hr)
<b>Max Input Resolution</b>	1280 x 1024/ 60 Hz (Analog), 1024 x 768/75 Hz (Digital)
<b>Recommend Input Resolution</b>	1280 x 768 / 60 Hz (Analog), 1024 x 768/60 Hz (Digital)
<b>H-Scanning Frequency</b>	31 ~ 66 kHz, auto-synchronous
<b>V-Scanning Frequency</b>	56 ~ 85 Hz, auto-synchronous
<b>Sync Compatibility</b>	Separate / Composite / SOG / Digital
<b>Video Input</b>	RGB Analog / Digital
<b>Input Connector</b>	15 Pin-D sub / DVI-D / RCA / S-VHS,D-TV
<b>VESA Plug and Play Level</b>	DDC 2B
<b>Memory Modes</b>	13 Factory Preset
<b>Power Supply</b>	90~264 V / AC (47 ~ 63Hz), Built-in Power Brick
<b>Power Consumption:</b>	Normal Operation 145 W Suspend/Standby 5 W Power Off Mode 1 W
<b>Front Panel Controls</b>	Source,Menu,Down,Up,Left,Right,Auto/Select,Power
<b>Source</b>	DVI DIGITAL, DSUB ANALOG, V1 (AV) , V2 (S)
<b>Digital On-Screen Controls</b>	Brightness, Contrast, Horizontal/Vertical Position, Clock, Phase, Language Select, Color Temp (9300K, 6500K, User), Image Size, OSD Lock, Transparent OSD, Zoom, Auto-Adjust, PIP On/Off, PIP Source, PIP Size, PIP Position, Information
<b>Light View</b>	Day (Text, Movie, Photo), Night (Text, Movie, Photo), User Mode
<b>Dimension (W x H x D)</b>	Net: 734 x 487 x 94 mm Gross: 852 x 667 x 283 mm
<b>Weight</b>	Net: 16.4 kg, Gross: 22 kg
<b>Wall/Arm Mount Type</b>	VESA Compliant
<b>Accessories</b>	Power cord, USB cable, DVI-D 19-pin cable, PC Audio cable, RCA Cable, Colorific Software/Manual/Install Disk Signal cable (15 pin D-sub to 15 pin D-sub)
<b>Optional Accessories</b>	Pedestal and/or Wall-Mount Stand
<b>Regulation Compliance</b>	TCO'99, UL1950, FCC-B, MPR-II, EPA Energy Star, IEC950, CSA, CE, TUV-GS, SEMKO, GOST, ISO 9241-3,7,8, C-TICK, VCCI-2
<b>Warranty</b>	3 Year Parts & Labour
<b>UPC#</b>	719192165656



The LG FLATRON L3000A is a masterpiece of design and engineering. The impressive 30" TFT LCD screen provides a sensational display for any image. With Super In-Plane Switching Technology, this display provides you with a 176° viewing angle, the widest in the industry! More features include Advanced PIP, LightView Function for optimal viewing, and optional remote control – this sleek 30" monitor is a technological work of art.



LG Electronics Canada Inc.

550 Matheson Blvd., Mississauga, Ontario L4Z 4G3 · 1-888-LGCANADA

©2002 LG Electronics Canada, Inc. All trademarks are property of their respective owners. Design and specifications subject to change without notice. 2/02



Life's Good

www.lg.ca